# DETROIT GLASSIG 40

# Two-Stroke Heavy Duty Diesel Engine Oil

Detroit Classic oil is a high performance, heavy-duty engine oil designed specifically for all two-stroke diesel engines manufactured by Detroit Corporation.

## Performance, Features and Benefits

#### · Low ash technology

Reduced risk of valve distress and build-up of combustion chamber deposits.

## • High thermal and oxidative stability

Maintains excellent standard of engine cleanliness.

# • Excellent protection against corrosion Less risk of scuffing and accelerated wear.

Advanced detergent technology

Long term deposit control and retention of TBN.

# • Shear stable SAE 40 & 50 monograde

Complete lubrication in all critical areas.

# **Main Applications**

#### Detroit two-stroke engines

Suitable for all Detroit two-stroke engines, in all applications including '149' engines used in mine haul trucks.

# **Specifications and Approvals**

- API: CF-II, CF
- DDC: 7SE 270 8810 (Sulphated Ash less than 0.8%) all equipment.

#### **Typical Physical Characteristics**

_//_ /				
Properties			Method	Detroit Classic
SAE Viscosity Grade				40
Kinematic Viscosity	at 40°C	cSt	ASTM D 445	138
Kinematic Viscosity	at 100°C	cSt	ASTM D 445	14.4
Viscosity Index			ASTM D 2270	103
Density	at 15°C	kg/m³	ASTM D 4052	899
Flash Point	(COC)	°C	ASTM D 92	250
Pour Point		°C	ASTM D 97	-15

These characteristics are typical of current production.

#### Advice

Advice on applications not covered in this leaflet may be obtained from your local Aftersales Representative.

#### **Health and Safety**

Detroit Classic is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on health and safety is available on the appropriate Safety Data Sheet which can be obtained from penskeps.com.

#### Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

